

Rec'd PCT/PTO 08 FEB 2005

PCT/GB 2003 / 0 0 3 3 4 6



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 03 SEP 2003

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 19 August 2003

BEST AVAILABLE COPY

An Executive Agency of the Department of Trade and Industry

Patents Form 1/77

item 1/77
rule 107THE PATENT OFFICE
A
10 AUG 2002The
Patent
Office

1/77

Request for grant of a patent

See the notes on the back of this form. You can also get
an explanatory leaflet from the Patent Office to help
you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference	11100P1 GB/JM		
2. Patent application number (The Patent Office will fill in this part)	0218605.4		
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Reckitt Benckiser (UK) Limited 103-105 Bath Road Slough Berkshire SL1 3UH United Kingdom Patents ADP number (if you know it) 07972136002 If the applicant is a corporate body, give the country/state of its incorporation England		
4. Title of the invention	Cosmetic article and related methods		
5. Name of your agent (if you have one)	John C. McKnight		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Reckitt Benckiser plc Group Patents Department Dansom Lane Hull HU8 7DS United Kingdom Patents ADP number (if you know it) 07800303001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application (day / month / year)		Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	Yes		

Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form	--
Description	24
Claim(s)	3
Abstract	1
Drawing(s)	2 + 2

CF

0. If you are also filing any of the following, state how many against each item.

Priority documents	
Translations of priority documents	
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	
Request for preliminary examination and search (Patents Form 9/77)	One
Request for substantive examination (Patents Form 10/77)	One
Any other documents (please specify)	FS2

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

John C. McKnight
John C. McKnight

9 August 2002

12. Name and daytime telephone number of Person to contact in the United Kingdom

John C. McKnight (01482) 583719

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patents Office.

Cosmetic article and related methods

This invention relates to hair removing products, to their manufacture and to methods of hair removal.

5

It is known to provide depilatory compositions in the form of lotions, creams or the like, which are applied to the skin with a spatula or other implement. After being left on the skin for a desired period of time the composition is removed, either by scraping or peeling the composition from the skin. The removed composition includes embedded hair debris where the hair has been chemically broken down, leaving a hairless region on the skin. In use, the composition is generally applied as a relatively thick coating, to the area where it is wished to remove hair, such as the legs or the axilla, and left in situ for around 5 to 10 minutes, for the hair to be chemically broken down. The composition is formulated so as to have a sufficiently high viscosity to prevent its flow away from the area to which it has been applied.

The operation of applying the depilatory composition, especially when in a paste or cream formulation, and removing it can be time consuming and awkward. Frequently, the composition has to be scraped carefully from the skin in order to remove all of the composition. This operation can irritate the skin and take a considerable length of time. Prolonged contact of the composition with the skin can itself irritate the skin.

30

Furthermore when a lotion, cream or the like is applied to certain areas of the body, such as the axilla, the user must be very careful to prevent the lotion or cream from

being transferred to other parts of the body, or to clothing.

- It would be preferable to provide a depilatory composition which needs minimal manipulation by a user, which is easy to apply accurately to the skin and which may be removed efficiently and with minimal effort by the user after the hair has been degraded.
- 10 It is known to provide epilatory compositions formed of viscoelastic materials. The viscoelastic materials may in certain embodiments be rosin-based. In other embodiments they may be sugar-based.
- 15 In some products the epilatory compositions may be supplied in the form of strips, retained between cellophane sheets. A box of several sheets is typically purchased. The cellophane sheets may have coatings of polyvinyl chloride, which acts as a barrier preventing the composition, or components of it, from migrating through the sheets; and also having the correct release properties for use. In use, the user peels away one of the cellophane sheets, presses the epilatory strip firmly onto the area to be plucked using the other cellophane sheet, then removes that sheet. The user then presses a strip, of fabric onto the epilatory strip, then pulls one end of the fabric sharply away from the skin. The hairs trapped in the composition are removed from the treated area along with, optimally, all of the composition, still attached to the fabric.
- 20
25
30

The use of epilatory strips has been successful but is not free of problems. One problem that has been reported is

that of the epilatory composition flowing from between the sheets in very warm weather, so that a customer purchasing a box of strips may encounter a messy, unusable mass of the hair removing composition, still fluid or re-
5 set, in the box.

By "epilatory" herein we mean able mechanically to remove hairs which are still intact, whether by breaking them where they are thinned or by pulling them out by their
10 roots.

By "depilatory" we mean able to degrade or dissolve hair, by chemical action.

15 Preferred embodiments of the present invention seek primarily to solve the aforementioned problems with existing products, in particular to provide easier application and removal of the compositions from the skin than existing depilatory compositions, yet without the
20 leakage problems associated with prior epilatory compositions in the form of strips.

According to a first aspect of the present invention there is provided a packaged hair removing product comprising a
25 container and a hair-removing layer therein, wherein the container comprises a sheet formed with a shallow well, the hair-removing layer being retained in the shallow well, the container further comprising a closure member which retains the hair-removing layer in the container,
30 the closure member being removable or displaceable from the container to permit removal of the hair-removing layer.

The composition may be in the form of a strip. The container may be sufficiently flexible for the strip to be applied to the skin, after removal or displacement of the closure member, whilst still in its shallow well. 5 Alternatively it may, for example, be in contact with a release sheet of the form used in the prior art, thereby to facilitate application.

Preferably, however, the layer is carried by a substrate, 10 the layer and the substrate being substantially inseparable, so as to form a "patch". Preferably the substrate protrudes beyond the layer. Suitably the substrate is dimensioned to protrude laterally from substantially the entire periphery of the hair-removing 15 layer.

By "patch" we mean an article comprising a substrate on which is carried a layer of hair-removing composition, which layer is designed to remain in contact with the 20 substrate during application, use and removal of the article.

The use of a packaged product to supply a hair-removing composition as a layer in a well, mitigates or eliminates 25 the prior problems described above. A layer of hair-removing composition is supplied, preferably as a self-supporting body, not as a lotion or cream, which may be messy to apply and may be spread to parts of body other than that from which it is desired to remove hair. It is 30 packaged within a well and retained between the sheet in which the well is formed, and the closure member. The risk of migration of the composition is thereby at the least substantially reduced, and preferably eliminated.

Preferably the recess is stepped, and has an inner, deeper region in which the layer is located and an adjoining, shallower region, in which projecting portion(s) of the substrate is/are located.

Preferably, therefore, the packaged hair-removing product comprises a container and a hair-removing patch therein, the hair-removing patch having a layer of hair-removing composition, carried on a substrate which projects laterally from at least a portion of the layer of hair-removing composition, wherein the container comprises a sheet formed with a recess, the recess having an inner region in which the layer of hair-removing composition is located and an outer region which abuts but is shallower than the inner region, and in which the lateral portion of the substrate is located, the package further comprising said closure member.

Suitably the substrate is a flexible sheet material capable of carrying the layer of depilatory composition. The sheet material may be porous, absorbent and/or fibrous such that the depilatory composition is partially absorbed into the carrier to provide anchorage of the layer on the substrate. Suitably layer and substrate are bonded such that one cannot be peeled from the other.

The substrate may be woven or non-woven. The substrate may comprise natural or synthetic material or mixtures thereof.

Suitable natural substrate materials include cellulosic material, such as cellulose per se or derived from wood

pulp, cotton, hemp, jute, flax and fibre mixtures thereof, for example.

Suitable synthetic substrates include rayon, polyesters,
5 polyurethanes, polyvinyl acetate, polyacrylates, polymethacrylates, polyamides, styrenes, styrene co-polymers, polyolefins, polyvinylchlorides, inorganic fibres, polyethylene, polypropylene, polyethylene terephthalate, nylons, and mixtures and co-polymers
10 thereof, for example.

The substrate may comprise more than one layer of sheet material. Each layer of sheet material may be constructed from the same or different materials. Suitably each layer
15 is laminated to an adjacent layer.

Suitably the substrate on which the layer may suitably be carried comprises a non-woven sheet material and is preferably a non-woven polyethylene layer.

20

Suitably the shape of a substrate employed corresponds to the shape of the hair-removing layer, although preferably not to size. Alternatively the shape of the substrate may be different to the shape of the layer.

25

Suitably, the layer of hair-removing composition is a layer of generally even thickness, preferably always within $\pm 10\%$ of the mean thickness.

30 Suitably the ratio of the smallest diameter of the layer to its mean thickness is at least 20, preferably at least 40.

Suitably the layer of hair-removing composition has a thickness of between 0.5mm and 2.0mm, preferably between 1.0mm and 1.5mm and especially substantially 1.2mm.

- 5 Suitably the layer is of a self-supporting body substantially without propensity to migrate from the locus to which it is applied, even when vertical, and removed from the package and carried by the skin, and thus somewhat warmed.

10

- The layer of hair-removing composition may be of any size and geometry, and may particularly be round, oval, rectangular, square, L-shaped, T-shaped, semi-circular, crescent-shaped, U-shaped or V-shaped. The shape of the
15 layer may be determined by the body area to which it is intended to be connected to in use. Thus, for example, for patches intended for hair removal from the axilla, an oval (including elliptical) shaped layer is preferable. For patches intended for hair removal from the upper lip a
20 crescent shaped layer is preferred.

Preferably the minimum diameter of an oval axilla patch is at least 40mm, more preferably at least 50mm, most preferably at least 60mm.

25

Preferably the minimum diameter of an oval axilla patch is up to 90mm, more preferably up to 80mm, most preferably up to 70mm.

- 30 Preferably the maximum diameter of an oval axilla patch is up to 170mm, more preferably up to 160mm, most preferably up to 150mm.

Preferably the maximum diameter of an oval axilla patch is at least 120mm, more preferably at least 130mm, most preferably at least 140mm.

- 5 The layer may comprise a peelable release layer connected to one side of the hair-removing layer. The other side may have a further peelable release layer or a said substrate, when the product is a patch. The release layer may comprise a peelable silicone sheet, or a peelable
10 plastics sheet.

Suitably the hair-removing composition comprises one or more depilatory agents which degrade and/or destroy hair. Suitable depilatory agents include sulphur compounds such
15 as potassium thioglycolate, dithioerythritol, thioglycerol, thioglycol, thioxanthine, thiosalicylic acid, N-acetyl-L-cysteine, lipoic acid, NaHSO_3 , Li_2S , Na_2S , K_2S , MgS , CaS , SrS , BaS , $(\text{NH}_4)_2\text{S}$, sodium dihydrolipoate
20 6,8-dithiooctanoate, sodium 6,8-dithiooctanoate, salts of hydrogen sulphide for example NaSH or KSH , thioglycolic acid, thioglycerol, 2-mercaptopropionic acid, 3-mercaptopropionic acid, thiomalic acid, ammonium thioglycolate, glyceryl monothioglycolate, monoethanolamine thioglycolate, monoethanolamine
25 thioglycolic acid, diammonium dithiodiglycolate, ammonium thiolactate, monoethanolamine thiolactate, thioglycolamide, homocysteine, cysteine, glutathione, dithiothreitol, dihydrolipoic acid, 1,3-dithiopropanol, thioglycolamide, glyceryl monothioglycolate,
30 thioglycolhydrazide, keratinase, hydrazine sulphate, hydrazine disulphate, triisocyanate, guanidine thioglycolate, calcium thioglycolate and/or cysteamine.

Preferably a depilatory composition comprises a thioglycolate, more preferably potassium thioglycolate, as a depilatory agent.

5 Suitably a depilatory agent is provided in the depilatory composition in an amount of between 1wt% and 10wt%, preferably between 1.5wt% and 8wt% and more preferably between 2wt% and 6wt% of the total weight of the composition.

10

Optionally a depilatory composition includes an accelerator that accelerates the rate of depilatory action of the depilatory agent, such as urea, thiourea, dimethyl isosorbide (DMI), ethoxydiglycol (Transcutol) or
15 methylpropyldiol (Mp diol). The depilatory composition preferably comprises from 5wt% to 15wt%, more preferably from 6wt% to 10wt% of an accelerator, when present.

Alternatively or additionally the hair-removing
20 composition is epilatory. Thus, the hair-removing composition may comprise a matrix or polymeric material, which suitably has properties which may be described as gel-like, waxy or viscous.

25 Preferably, the viscoelastic properties of the composition do not change substantially as a function of time, or by addition of a chemical compound. Preferably they do change, from viscous-dominated to elastic-dominated, as a function of frequency of applied stress.

30

Thus, the composition may comprise a polymeric material comprising a tackifying epilatory material, for example a tackifying aliphatic or aromatic resin, ethylene vinyl

acetate, styrene-butene-styrene, a tackifying block copolymer, or a mixture of polyvinyl alcohol and a gel-promoting agent, preferably boric acid, for example. Suitable tackifying resins include rosinaceous materials, for example a rosin ester and/or colophony.

Preferably the composition comprising polyvinyl alcohol is formulated to be a tacky viscous or gel-like material, at ambient temperature, not a rubber-like material or a material which sets in use to form a rubber-like material, in an unstressed condition, at ambient temperature. Preferably the composition is formulated to become elastic on being abruptly stressed, at body temperature, so that it may be peeled from the skin as a sheet. Preferably the composition is formulated to be tacky, at ambient temperature.

Preferably, the polyvinyl alcohol is of molecular weight M_w at least at least 1,000 g/mol, more preferably at least 10,000 g/mol, and most preferably at least 20,000 g/mol (mean weights of the molar masses determined by Gel Permeation Chromatography).

Preferably the polyvinyl alcohol is of molecular weight M_w up to 500,000 g/mol, more preferably up to 200,000 g/mol, and most preferably up to 40,000 g/mol (determined as above).

Preferably the polyvinyl alcohol is hydrolysed to a degree of hydrolysis of at least 70%, more preferably at least 87%, and most preferably at least 97%.

Suitably the polyvinyl alcohol is present in an amount of between 0.1 wt% and 25wt%, preferably between 1wt% and 15wt%, more preferably between 2wt% and 10wt% and most preferably between 4wt% and 8wt% of the total weight of the composition.

Preferably a cosmetically-acceptable gel-promoting agent is employed with the polyvinyl alcohol.

10 A preferred class of gel-promoting agent is boron-containing compounds, especially acids and salts, for examples borates and boric acid. Favoured borates include perborates, metaborates and tetraborates (e.g. borax). Most preferred as a gel-promoting agent is boric acid.

15

Another suitable class of gel-promoting agent is organic azo dyes, for example Congo Red (sodium diphenyldiazo-bis-naphthylamine-sulphonate), benzopurpurine 4B, Congo Corinth G and benzoazurine G.

20

Other suitable gel-promoting agent may include: germanic acid and germanates; titanium salts and esters, particularly titanium IV-triethanolamine; chromates; vanadates; Group IB metal salts, particularly cupric salts; mono- and di-aldehydes (e.g. glutaraldehyde); 25 dicarboxylic acids (e.g. maleic acid, oxalic acid, malonic acid and succinic acid); tricarboxylic acids (e.g. citric acid); phenolic compounds (e.g. resorcinol, catechol, phloroglucinol, salicylanilide, gallic acid and 2,4-dihydrobenzoic acid); polyacroleine; mono- and di- 30 isocyanates (e.g. forming substituted carbamates); divinyl sulphate and other divinyl esters; and glycidyl and other difunctional methacrylates.

When the hair-removing composition comprises a mixture of a gel-promoting agent and polyvinyl alcohol, suitably the gel-promoting agent is present in an amount of between
5 0.01wt% and 1wt% of the total weight of the composition, preferably between 0.02wt% and 0.5wt%, more preferably between 0.05wt% and 0.25wt%.

Preferably when the hair-removing composition comprises
10 polyvinyl alcohol the composition is an aqueous composition comprising water in an amount between 40wt% and 90wt%, preferably between 50wt% and 70wt% and more preferably between 50wt% and 60wt% of the total weight of the composition.

15 The amount of polyvinyl alcohol present in a preferred hair-removing composition of the invention, and the amount of a gel-promoting agent when present, will be in part determined by the desired viscoelastic properties of the
20 composition. In order to further modify the viscosity of the depilatory composition, the composition may further comprise a polyhydric alcohol. Suitable polyhydric alcohols include glycerol, propylene glycol, mannitol, sorbitol, glucose, fructose, sucrose, propane diol and the
25 like, but is preferably propylene glycol. Suitably the polyhydric alcohol is present in an amount of between 0.01wt% and 50wt%, preferably between 1wt% and 40wt% and preferably between 5wt% and 30wt% of the total weight of the composition.

30

When, as is preferred, boric acid is present as a gel-promoting agent, without being bound by any theory it is thought that polyvinyl alcohol reacts with the boric acid

by a so-called "di-diol" complexation which is ion-assisted from the borate. Two diol units of PVA are thought to react with one borate ion to form a cross-link. It is thought that the PVA-borate crosslinking mechanism is divided into two sections; a mono-diol complexion and a cross-link formation.

Once a borate ion is attached to a polymer chain, it is believed to behave as a polyelectrolyte unless the borate ion is removed from the chain or is bound to another diol unit as a crosslinking point. In that case, a significant contribution of electrostatic repulsion between the monodiol units of the PVA chain is expected resulting in an extension of the individual polymer chains and the formation of a gel at a given concentration of PVA.

This phenomenon depends on the reactants, such as PVA concentration, borate ion concentration, and temperature.

A similar mechanism is thought to apply when other gel-promoting agents are employed.

"Boric acid" herein may be one or more of orthoboric (also known as boracic) acid, metaboric acid and tetraboric (also known as pyroboric) acid. Most preferred is orthoboric acid, H_3BO_3 .

In a hair-removing composition having epilatory qualities, it is preferred that at low frequency of applied stress its viscous modulus exceeds its elastic modulus - so that it is liquid-like to put on - and at higher frequency of applied stress its elastic modulus exceeds its viscous modulus - so that it can be removed as a piece, e.g. by an

abrupt peeling action. The point at which the viscous and elastic moduli are equal is called the crossover point (or gel point). Under reference conditions - temperature, 30°C; applied stress 5Pa; using an SR
5 rheometer as described later - the crossover point is preferably at 1 rad/s or below, most preferably at 0.2 rad/s or below.

Preferably the value of the elastic and viscous moduli at
10 the crossover point is less than 300 Pa, more preferably less than 100 Pa.

Preferably the elastic modulus above the crossover point is higher than the viscous modulus at all frequencies up
15 to 10 rad/s, more preferably at all frequencies up to 100 rad/s; and may also be higher than the viscous modulus at higher frequencies.

Preferably the value of the elastic modulus is less than
20 300 Pa, more preferably less than 100 Pa, at all frequencies up to 10 rad/s, more preferably at all frequencies up to 100 rad/s.

Preferably the elastic modulus reaches a level or gently
25 ascending plateau (the "rubbery plateau") with rising frequency above the crossover point.

To summarise, below the crossover point the viscous property predominates and the composition is liquid-like
30 and highly suitable for application to skin and hairs. Above the crossover point the elastic property predominates and the composition is rubber-like, and

highly suitable for good removal, carrying with it removed hairs.

5 The elastic modulus G' (sometimes known as the storage modulus) corresponds to the energy which can be stored and released by a bulk material. The viscous modulus G'' (sometimes known as the loss modulus) corresponds to the energy dissipated by a bulk material due to friction between its macromolecules when it is deformed.

10

$$G' = \frac{\sigma}{\gamma} \cos \delta$$

$$G'' = \frac{\sigma}{\gamma} \sin \delta$$

15

wherein σ is the stress amplitude, γ is the strain amplitude and δ is the out-of-phase coefficient.

20 The measurements quoted later are based on studies carried out into the rheology of the viscoelastic compositions in order to obtain a better understanding of their adhesive behaviour and their suitability as epilatory materials. These studies involved subjecting the materials to dynamic investigations in which a sinusoidal strain at defined frequencies was applied to the materials and the resulting output force was measured. In these studies a stress control rheometer was used, the SR rheometer commercially available from the company Rheometrics, using parallel plate geometry of 40 mm in diameter. The sample to be tested is squeezed between the plates, until there is a gap between the plates of 1mm, and so a sample thickness of 1 mm. Material squeezed out from between the plates is removed.

25

30

The output force from the rheometer includes an in-phase elastic component G' and an out-of-phase viscous component G'' . The output force can be expressed as follows.

5

$$\begin{aligned}\sigma &= \sigma \sin(t\omega + \delta) \\ &= \sigma \cos\delta \sin t\omega + \sigma \sin\delta \cos t\omega\end{aligned}$$

where ω is the test frequency and t is the time.

10

The hair-removing composition, whether having an epilatory and/or depilatory property, may contain further ingredients such as a surfactant; a colorant; a fragrance or perfume; a filler such as talc, calcium carbonate or a fibrous material; a preservative; or a dye, as are conventionally included in cosmetic compositions.

Preferably the hair-removing composition, whether having an epilatory and/or depilatory property, is alkaline, more preferably of pH in the range 10 to 14, most preferably of pH in the range 11 to 13. An especially preferred pH range of the composition is between pH 12 and 12.5.

Suitably the composition comprises a pH regulator, to regulate the pH of the composition within the preferred ranges. Suitable pH regulators are bases, and may include arginine, especially L-arginine; silicates, especially sodium or potassium silicates; lime; polyethylenimine; potassium hydroxide; calcium hydroxide; lithium hydroxide; and sodium hydroxide.

The pH regulator is thought to assist in promoting the action of a depilatory agent, when present, through

maintaining optimum pH for action of the agent on keratin/hair.

A particularly preferred hair-removing composition for use
5 in a patch of the invention comprises an alkali metal (preferably potassium) hydroxide, lime, and an alkali metal (preferably potassium) thioglycolate, polyvinyl alcohol, boric acid and propylene glycol.

10 According to a second aspect of the invention there is provided a method of depilation comprising: (a) removing or displacing the closure member of the package as defined above; (b) removing the hair-removing layer from the product of the first aspect and applying it to the skin;
15 and (c) removing the hair-removing layer from the skin.

Preferably the layer is depilatory and there is an intermediate step (b1) of leaving the layer on the skin for a prescribed period of time.

20 The prescribed period of time in step (b) will depend on the depilatory composition, but may typically be between 60 seconds and 1200 seconds, preferably 180 seconds and 900 seconds and more preferably between 300 seconds and
25 600 seconds.

According to a third aspect of the invention there is provided a method of manufacturing the product of the first aspect comprising the step of introducing hair-
30 removing composition into the well as a warm, flowable composition and applying the closure member.

Preferably a product of the first aspect of the invention is protected from air until it is used. Preferably the container is airtight. The closure member is preferably in the form of a polymeric or metallic foil, or a metallised polymeric foil, preferably which is removable by a peeling action, in order to access the layer. The sheet is preferably of a gas-impermeable thermoplastics material.

10 The manufacturing method may thus comprise a step (c) of applying a closure member to enclose the layer within an airtight package, preferably enclosing a vacuum or inert atmosphere.

15 The invention will now be described further with reference to the following non-limiting examples.

The following materials were used in the examples:

Deionised water

20 Polyvinylalcohol (PVA) - PVA Mowiol 4-98 available, from Clariant

Boric acid - 4% solution w/w in water

Propylene glycol

Potassium thioglycolate -30% w/w solution in water

25 Potassium hydroxide - a 50% w/w solution in water

Calcium hydroxide

Alcohol ethoxylate 11EO

Fragrance - floral tones

30 Example 1

The following ingredients/amounts were used:

Ingredient	w/w total composition (%)
Deionised water	56.18
PVA	6
Boric acid (4%)	0.12
Propylene glycol	22.1
Potassium thioglycolate (30%)	10
Potassium hydroxide (50%)	4.90
Fragrance	0.7

The required proportion of deionised water was heated to 80°C in a reactor. The PVA was added and the mixture was stirred in the reactor vessel for the necessary time for all of the PVA to be dissolved. The mixture was then cooled down to 40°C and a solution of boric acid was added to it. After 30 minutes of stirring, the propylene glycol was introduced with stirring, then the potassium thioglycolate, followed by the fragrance. Finally, the potassium hydroxide was introduced dropwise with stirring. The resulting solution was then transferred to a suitable storage container.

The resultant formulation had a pH of 12.5 and was in a form of a viscoelastic tacky hydrogel. Its mechanical properties, determined as described above, are shown in Figures 1 and 2.

Thus, measurements were made by an SR rheometer from rheometric, in a dynamic mode. G' and G'' are respectively the elastic and viscous modulus characterising the tackiness of the gel.

Figure 1 is a graph of G' and G'' against frequency, as described above.

Figure 2 is a graph of G' and G'' against test temperature, under conditions of 5 Pa stress applied at 5 rad/s, with 5 minute test periods.

It will be seen from Figure 1 that at low test frequencies the viscous modulus exceeds the elastic modulus. At higher test temperatures the elastic modulus exceeds the viscous modulus. The crossover point is at a modulus of 19.8 Pa and a frequency of 0.126 rad/s. Beyond the crossover point the elastic modulus follows a gently ascending plateau, as the test frequency increases. Figure 2 shows that under the test conditions the elastic modulus exceeds the viscous modulus at all temperatures up to 39.7°C, the moduli then both being 2.18 Pa. This is a good indication that the patch will be suitable for use under all normal ambient conditions.

20

Figures 3, 4 and 5 show a patch intended for removal of axillary hair, and a package therefor. Figure 3 is a plan view of a tray part of a package, not containing a patch. Figure 4 is a side sectional view of the tray part of the package, not containing a patch, along view A-A' shown in Figure 3. Figure 5 is a corresponding view, with the tray containing a patch.

As may be seen most clearly in Figure 4 the package includes a moulded tray part having a central, wide, shallow, well 2, oval in plan view. The tray part is of a gas impermeable plastics material, manufactured as a sheet but shaped to form the tray part by thermoforming.

The warm composition of Example 1 is injected into the well 2, in a controlled amount such that it just fills the well and no more (see Figure 5). Beyond the well 2, and extending all around it, is a ledge 4, of rectangular exterior shape. The non-woven textile substrate 5 of matching rectangular shape is laid onto the ledge 4 and over the depilatory composition 2, thereby forming the patch (see Figure 5). Beyond this ledge 4 and extending all around it there is an uppermost ledge 6. The uppermost ledge is the periphery of the tray-like part and is rectangular, but with rounded corners. A release layer in the form of a closure foil 7, of metal, polymeric or metallised polymeric material is laid onto this uppermost ledge 6 so as to form a seal against it. As this happens the air in the package is flushed out with nitrogen. The seal is achieved in this embodiment by means of a heat-activated adhesive. The rectangular shaded zone 8 in Figure 3 denotes the seal. The seal is of a high quality; air cannot pass it to enter the package.

The combination of the gas-impermeable tray and foil, the impermeable seal between them and the exclusion of oxygen within the package all serve to shield the depilatory composition - in particular the potassium thioglycolate component - from the degradative effects of the oxygen in the external atmosphere.

It will be seen that at one end of the package there is a region 10 beyond the seal. In this region 10 the uppermost ledge 6 is wider than elsewhere and the foil is adhered only to an inner band of this widened ledge. Thus, in this region the foil may be gripped by the user

in order to tear it away, allowing the user to remove the patch. In Figure 5 the foil 7 is shown partly removed. When it is removed the non-woven substrate 5 may be grasped at its periphery in order to lift the patch from the package. The patch may then be pressed onto an axilla.

In this embodiment the smallest diameter of the well, that is, of depilatory layer, is 65mm. The largest diameter is 145mm. The size of the substrate is 170mm x 90mm. The size of the pack is 192mm by 105mm. The outer ledge 6 is 7.5mm wide around three sides but the other side, having the foil edge which can be grasped for peeling away, is 14.5mm wide.

The liquid-like properties at low frequency assist the wetting process. The patch is comfortable to wear. The substrate prevents undesirable migration of the depilatory composition.

After 5 minutes the patch is lifted off, wherein the hair previously present on the skin is found to be substantially completely removed, and hair debris can be seen on the depilatory patch. The act of peeling off the patch gives a mild epilatory effect, carrying off hairs which have been thinned by the depilatory agent. The act of peeling off the patch corresponds to a higher frequency condition in which the elastic modulus predominates, aiding the clean removal of the patch as a rubber-like body, with the mild epilatory effect mentioned above.

Example 2

The following ingredients/amounts were used:

5

Ingredient	w/w total composition (%)
PVA	4
Deionised water	59.88
Boric acid (4%)	0.12
Thioglycolic acid (30%)	10
Propylene glycol	22.1
Fragrance	0.7
Alcohol ethoxylate 11EO	1.5
Calcium hydroxide	1.7
Total	100.00%

They were used to make a depilatory composition also having some epilatory properties, in the manner described in Example 1, for conjoining to a substrate to form a depilatory patch.

10

Example 3

The following ingredients/amounts were used:

5

Ingredient	w/w total composition (%)
PVA	8
Deionised water	55.88
Boric acid (4%)	0.12
Thioglycolic acid (30%)	10
Propylene glycol	22.1
Fragrance	0.7
Alcohol ethoxylate 11EO	1.5
Calcium hydroxide	1.7
Total	100.00%

They were used to make a depilatory composition also with some epilatory properties in the manner described in Example 1, for conjoining to a substrate to form a
10 depilatory patch.

Claims

1. A packaged hair removing product comprising a container and a hair-removing layer therein, wherein the
5 container comprises a sheet formed with a shallow well, the hair-removing layer being retained in the shallow well, the container further comprising a closure member which retains the hair-removing layer in the container, the closure member being removable or displaceable from
10 the container to permit removal of the hair-removing layer.
2. A product as claimed in Claim 1, wherein the layer is in inseparable contact with a substrate, to form a patch.
- 15 3. A product as claimed in Claim 1 or 2, wherein the substrate projects laterally from the layer and the sheet has a stepped recess by accommodate snugly the layer and the projection of the substrate beyond the layer.
- 20 4. A product as claimed in any preceding claim, wherein the sheet has a flange or rim around the whole of its periphery against which the closure member is sealed.
- 25 5. A product as claimed in any preceding claim, wherein the layer has a depilatory action.
6. A product as claimed in any preceding claim, wherein the depilatory composition has an epilatory function.
- 30 7. A product as claimed in any preceding claim, wherein the layer comprises a polymeric material.

8. A product as claimed in Claim 7, wherein the polymeric material comprises polyvinyl alcohol.

9. A product as claimed in Claim 8, wherein a
5 cosmetically acceptable gel-promoting agent is employed with the polyvinyl alcohol.

10. A product as claimed in Claim 9, wherein the
cosmetically acceptable gel-promoting agent is a borate or
10 boric acid.

11. A product as claimed in Claim 8, 9 or 10, wherein the depilatory composition is an aqueous composition comprising water in an amount between 40wt% and 90wt%, of
15 the total weight of the composition.

12. A product as claimed in any of Claims 8 to 11, wherein the composition further comprises a polyhydric alcohol.

20 13. A product as claimed in any preceding claim, wherein the depilatory composition is alkaline.

14. A method of depilation comprising (a) removing or displacing a closure member of a product as claimed in any
25 preceding claim, to access the layer; (b) applying the layer to the skin; and (c) removing the layer from the skin.

15. A method of manufacturing a product as claimed in any
30 of Claims 1 to 13, comprising the steps of: (a) introducing the hair-removing composition as a warm, flowable composition into the shallow well; and (b) closing the container by means of the closure member.

16. A hair-removing product substantially as described herein.

5 17. A method of depilation substantially as described herein.

18. A method of manufacturing a hair-removing product substantially as described herein

AbstractCosmetic article and related methods

5

The present invention provides a depilatory patch comprising a layer of depilatory composition carried by a substrate. The depilatory patch is arranged, in use, to be applied to the skin of a user and left for a prescribed
10 time period before being removed. The depilatory composition acts to degrade or destroy hair on the skin where the patch has been applied. The invention also extends to methods of manufacturing depilatory patches of the invention, and to depilatory methods using such
15 patches.

(Figure 5)

1/2




Fig. 2







Fig. 1

2/2

ORIGINAL NOT TO SCALE



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.